OUTLANDER™ 330 H.O. 4x4



Laurentian green | Viper red | Camo

ENGINE

Manufacturer	Rotax®
Type	4-stroke, 1 cylinder, dougle overhead cam
Displacement	325 cc
Bore & Stroke	82 × 62 mm
Torque @ rpm	25 Nm @ 6700 rpm
Starter	Electric start with auxiliary recoil
Lubrication	Wet sump
Decompressor	Automatic
Carburetor	Mikuni BSR33
Electrical output - ACG	400 W range - DENSO

BRAKES

Handlebar control	Hydraulic brakes front and rear
Foot control	Rear wheels brake
Front brake type/qty	2 drilled hydraulic discs
Rear brake type/qty	1 drilled hydraulic disc
Parking device	Side handlebar control (hydraulic) and sub-transmission park

SUSPENSION

FRONT SUSPENSION	
Front suspension type	Independent suspension – Mc Pherson type
Front suspension travel	7.01 in. (178 mm)
REAR SUSPENSION	
Rear suspension type	Independent suspension - Trailing arms with torsionally-tied swaybar
Rear suspension travel	8 in. (203.2 mm)

COOLING / DRIVE TRAIN

Type	Liquid cooled
Radiator	Front-mounted
Ethylene-glycol / water concentration	50/50
Transmission	CVT transfer with sub-transmission Low, High, Neutral, Reverse & Park with selectable 2W/4WD
Clutch type	Continuously Variable Transmission (CVT)
Front differential	Shaft driven / single auto-lock differential (pump driven) (Visco-Lok)
Rear axle	Shaft driven / independent rear axle

EQUIPMENT / ELECTRICAL

DC outlets	Lighter type in console (cellular phone use) Standard connector in the back (15 A)
Racks	High strength plastic front and rear racks
LIGHTING	On-Off switch combined with ignition key
Front	2 fender-mounted headlamps (30 W), 2 fender-mounted amber reflectors
Rear	Running/brake light, 2 fender-mounted amber reflectors
Battery	12 V, 13 Ah (dry type)

DIMENSIONS / CAPACITIES OVERALL

Overall height	45 in. (1143 mm)
Overall length	86 in. (2184 mm)
Overall width	46 in. (1168 mm)
Wheel base	49 in. (1244 mm)
Wheel track - front	38 in. (965 mm)
Wheel track - rear	36 in. (914 mm)
Turning radius	72 in. (1829 mm)
Fuel tank	4.2 US gal. (16 L)
Front tires	25 × 8 × 12 in. (635 × 203 × 305 mm)
Rear tires	25 × 10 × 12 in. (635 × 254 × 305 mm)
Front wheels	12 in. diam. × 6 in. wide (305 × 152 mm)
Rear wheels	12 in. diam. × 7.5 in. wide (305 × 190.5 mm)

LOADING CAPACITY	
Front rack	90 lbs (40 kg)
Rear rack	175 lbs (80 kg)
Total vehicle load allowed	500 lbs (230 kg)
Towing capacity	1100 lbs (500 kg)
GROUND CLEARANCE	
Front & under engine	9.3 in. (236 mm)
Rear axle	9.3 in. (236 mm)
VEHICLE WEIGHT	
Dry vehicle weight	592 lbs (269 kg)
GVWR (Gross Vehicle Weight Rating)	1000 lbs (454 kg)

INSTRUMENTATION

Gauge	Speedometer, Odometer, Trip odometer, Hour.
Fuel gauge	Mechanical type
Pilot lamps	Reverse-Neutral, Oil pressure / water temperature, Low and High beam, 4x4 and Park

OUTLANDER

BOMBARDIER ATV

Follow No One.

www.bombardier-atv.com 1-877-4-MY-RIDE 1-877-469-7433 ©2002 Bombardier Inc. All rights reserved. ™: Trademarks and ®: Registered Trademarks of Bombardier Inc. or its subsidiaries. In the U.S.A., products are distributed by Bombardier Motor Corporation of America. Bombardier reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. ATVs with engine sizes of greater than 90 cc are recommended for use only by those aged 16 and older. Bombardier highly recommends that all ATV riders take a training course. For safety and training information, see your dealer or in the U.S., call the ATV Safety Institute at 1 800 887-2887. In Canada, call the Canadian Safety Council at (613) 739-1535 ext. 227. **ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never ride on paved surfaces or public roads. Never carry passengers on an ATV not specifically designed for such use. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain.**

Printed in Canada 716000203